



North Carolina Department of Environment and Natural Resources

Michael F. Easley, Governor

Division of Air Quality

William G. Ross, Jr., Secretary

B. Keith Overcash, P.E., Director

DATE, 2008

Mr. Bernard Hodges
President
Wade Manufacturing Company
Highway 74 East
Wadesboro, North Carolina 28170

Dear Mr. Hodges:

**SUBJECT: Air Quality Permit No. 03577T16
Facility ID: 0400016
Wade Manufacturing Company
Wadesboro, North Carolina
Anson County
Fee Class: Title V**

In accordance with your completed Air Quality Permit Application for a renewal of a Title V permit received October 2, 2007, we are forwarding herewith Air Quality Permit No. **03577T16** to Wade Manufacturing Company, Highway 74 East, Wadesboro, North Carolina authorizing the construction and operation, of the emission source(s) and associated air pollution control device(s) specified herein. Additionally, any emissions activities determined from your Air Quality Permit Application as being insignificant per 15A North Carolina Administrative Code 2Q .0503(8) have been listed for informational purposes as an "ATTACHMENT." Please note the requirements for the annual compliance certification are contained in General Condition P in Section 3 of Part I. **The current owner is responsible for submitting a compliance certification for the entire year regardless of who owned the facility during the year.**

As the designated responsible official it is your responsibility to review, understand, and abide by all of the terms and conditions of the attached permit. It is also your responsibility to ensure that any person who operates any emission source and associated air pollution control device subject to any term or condition of the attached permit reviews, understands, and abides by the condition(s) of the attached permit that are applicable to that particular emission source.

If any parts, requirements, or limitations contained in this Air Quality Permit are unacceptable to you, you have the right to request a formal adjudicatory hearing within 30 days following receipt of this permit, identifying the specific issues to be contested. This hearing request must be in the form of a written petition, conforming to NCGS (North Carolina General Statutes) 150B-23, and filed with **both** the Office of Administrative Hearings,

Permitting Section

1641 Mail Service Center, Raleigh, North Carolina 27699-1641

2728 Capital Blvd., Raleigh, North Carolina 27604

Phone: 919-715-6235 / FAX 919-733-5317 / Internet: <http://daq.state.nc.us/>

An Equal Opportunity/Affirmative Action Employer – 50% Recycled/10% Post Consumer Paper

One
North Carolina
Naturally

Mr. Bernard Hodges

DATE, 2008

Page 2

6714 Mail Service Center, Raleigh, North Carolina 27699-6714 and the Division of Air Quality, Permitting Section, 1641 Mail Service Center, Raleigh, North Carolina 27699-1641. The form for requesting a formal adjudicatory hearing may be obtained upon request from the Office of Administrative Hearings. Please note that this permit will be stayed in its entirety upon receipt of the request for a hearing Unless a request for a hearing is made pursuant to NCGS 150B-23, this Air Quality Permit shall be final and binding 30 days after issuance.

You may request modification of your Air Quality Permit through informal means pursuant to NCGS 150B-22. This request must be submitted in writing to the Director and must identify the specific provisions or issues for which the modification is sought. Please note that this Air Quality Permit will become final and binding regardless of a request for informal modification unless a request for a hearing is also made under NCGS 150B-23.

The construction of new air pollution emission source(s) and associated air pollution control device(s), or modifications to the emission source(s) and air pollution control device(s) described in this permit must be covered under an Air Quality Permit issued by the Division of Air Quality prior to construction unless the Permittee has fulfilled the requirements of GS 143-215-108A(b) and received written approval from the Director of the Division of Air Quality to commence construction. Failure to receive an Air Quality Permit or written approval prior to commencing construction is a violation of GS 143-215.108A and may subject the Permittee to civil or criminal penalties as described in GS 143-215.114A and 143-215.114B.

This Air Quality Permit shall be effective from DATE, 2007 until DATE, 2013, is nontransferable to future owners and operators, and shall be subject to the conditions and limitations as specified therein.

Should you have any questions concerning this matter, please contact Mr. Michael W. Benson, E.I.T. (mike.benson@ncmail.net) at (919) 715-6272.

Sincerely yours,

Donald R. van der Vaart, Ph.D., P.E.

Enclosure

c: EPA Region IV w/review
Fayetteville Regional Office
Central Files

ATTACHMENT to cover letter to Air Quality Permit Number **03577T16**

The following table describes the modifications to the current permit as part of the modification process.

Old Page(s)*	New Page(s)	Condition/Item	Description of Change(s)
Part I			
Global	Global	N/A	<ul style="list-style-type: none"> • Change permit revision number to T16 • Change the issuance/effective dates of the permit • Amend the application number and complete date
attachment	attachment	N/A	moved from back of permit to cover letter
3	3	table	changed PR1 to steam heated
6	6	table	removal of retention pond shield disclaimer
6	7	2.1.A	changed 2D .0530 to 2Q .0317
8	9	2.1.B	changed 2D .0530 to 2Q .0317
9	11	2.1.C	changed 2D .0530 to 2Q .0317
11	13	2.1.D	changed 2D .0530 to 2Q .0317 changed natural gas-fired to steam heated for PR1
12	15	2.1.E	changed 2D .0530 to 2Q .0317
16	21	2.2.A	changed PR1 to steam heated
18	22	2.2.B	changed 2D .0530 to 2Q .0317
19	23	2.2.C	changed 2D .0530 to 2Q .0317 changed natural gas-fired to steam heated for PR1
27-37	26-36	3	updated General Conditions

*page numbers approximate as previous file was extremely corrupted

ATTACHMENT to cover letter to Air Quality Permit Number **03577T16**

Insignificant Activities under 15A NCAC 2Q .0503(8)

Emission Source ID No.	Emission Source Description
I-SD1 and I-SD2	Steam heated slasher dryers
I-DFM	Dye and finish mixing room

1. Because an activity is insignificant does not mean that the activity is exempted from an applicable requirement or that the owner or operator of the source is exempted from demonstrating compliance with any applicable requirement.
2. When applicable, emissions from stationary source activities identified above shall be included in determining compliance with the permit requirements for toxic air pollutants under 15A NCAC 2D .1100 "Control of Toxic Air Pollutants" or 2Q .0711 "Emission Rates Requiring a Permit".

**State of North Carolina,
Department of Environment,
and Natural Resources**

Division of Air Quality



AIR QUALITY PERMIT

Permit No.	Replaces Permit No.(s)	Effective Date	Expiration Date
03577T16	03577T15	DATE, 2008	DATE, 2013

Until such time as this permit expires or is modified or revoked, the below named Permittee is permitted to construct and operate the emission source(s) and associated air pollution control device(s) specified herein, in accordance with the terms, conditions, and limitations within this permit. This permit is issued under the provisions of Article 21B of Chapter 143, General Statutes of North Carolina as amended, and Title 15A North Carolina Administrative Codes (15A NCAC), Subchapters 2D and 2Q, and other applicable Laws.

Pursuant to Title 15A NCAC, Subchapter 2Q, the Permittee shall not construct, operate, or modify any emission source(s) or air pollution control device(s) without having first submitted a complete Air Quality Permit Application to the permitting authority and received an Air Quality Permit, except as provided in this permit.

Permittee: **Wade Manufacturing Company**
Facility ID: **0400016**

Facility Site Location: **Highway 74 East**
City, County, State, Zip: **Wadesboro, Anson County, North Carolina 28170**

Mailing Address: **P.O. Box 32**
City, State, Zip: **Wadesboro, North Carolina 28170**

Application Number: **0400016.07A**
Complete Application Date: **October 2, 2007**
Primary SIC Code: **2290**
Division of Air Quality, **Fayetteville Regional Office**
Regional Office Address: **Systel Building, Suite 714**
Fayetteville, North Carolina 28301

Permit issued this the Xth day of MONTH, 2008

Donald R. van der Vaart, Ph.D., P.E., Chief, Air Permits Section
By Authority of the Environmental Management Commission

Table Of Contents

PART I

SECTION 1: PERMITTED EMISSION SOURCE(S) AND ASSOCIATED AIR POLLUTION CONTROL DEVICE(S) AND APPURTENANCES

SECTION 2: SPECIFIC LIMITATIONS AND CONDITIONS

2.1 - Emission Sources Specific Limitations and Conditions
(Including specific requirements, testing, monitoring, recordkeeping, and reporting requirements)

2.2 - Multiple Emission Sources Specific Limitations and Conditions
(Including specific requirements, testing, monitoring, recordkeeping, and reporting requirements)

SECTION 3: GENERAL PERMIT CONDITIONS

ATTACHMENT

List of Acronyms

PART II

This permit contains no Part II.

PART I

The Division of Air Quality (DAQ), the United States Environmental Protection Agency (EPA), and citizens as defined under the Federal Clean Air Act have the authority to enforce the terms, conditions, and limitations contained in Part I of this permit unless otherwise specified.

Under Title 15A NCAC 2Q, the operation of emission source(s) and associated air pollution control device(s) and appurtenances listed in Part I of this permit is based on plans, specifications, operating parameters, and other information as submitted in the Air Quality Permit Application.

SECTION 1- PERMITTED EMISSION SOURCES AND ASSOCIATED AIR POLLUTION CONTROL DEVICES AND APPURTENANCES

The following table contains a summary of all permitted emission sources and associated air pollution control devices and appurtenances:

Emission Source ID No.	Emission Source Description	Control Device ID No.	Control Device Description
B1	One natural gas/ No. 6 fuel oil-fired boiler (72 million Btu per hour heat input capacity)	N/A	N/A
B2	One natural gas/No. 6 fuel oil-fired boiler (24.76 million Btu per hour heat input)	N/A	N/A
PR1	One steam heated textile roller printer (3,600 pounds of cloth per hour process capacity) consisting of: a) 10 print stations b) 1 steam heated dryer	N/A	N/A
PR3	One textile roller printer (3,600 pounds of cloth per hour process capacity) consisting of: a) 8 print stations b) 1 natural gas-fired dryer (2 million Btu per hour heat input)	N/A	N/A
PR6	One textile roller printer (3,600 pounds of cloth per hour process capacity) consisting of: a) 8 print stations b) 1 natural gas-fired dryer (2 million Btu per hour heat input)	N/A	N/A

Emission Source ID No.	Emission Source Description	Control Device ID No.	Control Device Description
PR4	One textile screen printer (3,600 pounds of cloth per hour process capacity) consisting of: a) 8 rotary screen printing stations b) 1 natural gas-fired dryer (4.8 million Btu per hour heat input) with four zones	N/A	N/A
PR5	One textile screen printer (3,600 pounds of cloth per hour process capacity) consisting of: a) 12 rotary screen printing stations b) 1 natural gas-fired dryer (4.8 million Btu per hour heat input) with four zones	N/A	N/A
TEN1	One finishing range (4,320 pounds of cloth per hour process capacity) consisting of: a) 1 pad applied finishing station b) 1 natural gas-fired 8.5 million Btu per hour three zone tenter frame oven	N/A	N/A
TEN2	One finishing range (5,760 pounds of cloth per hour process capacity) consisting of: a) 1 pad applied finishing station b) 1 natural gas-fired 12.0 million Btu per hour eight zone tenter frame oven	N/A	N/A
TEN3	One finishing range (4,320 pounds of cloth per hour process capacity) consisting of: a) 1 pad applied finishing station b) 1 natural gas-fired 6.0 million Btu per hour two zone tenter frame oven	N/A	N/A
J-BOX, BL1, and TEN4	One bleach range and one natural gas-fired 8.5 million Btu per hour three zone finishing range	N/A	N/A
CR1	Steam heated cotton dye range	N/A	N/A
PIG1	One pigment range (4,800 pounds of cloth per hour process capacity) consisting of: a) 1 natural gas-fired 4.0 million Btu per hour predryer b) 1 pad applied ink dyeing station c) 1 steam heated dryer	N/A	N/A
Emission Source ID No.	Emission Source Description	Control Device ID No.	Control Device Description

TR1	One thermasol range (4,800 pounds of cloth per hour process capacity) consisting of: a) 1 pad applied finishing station b) 1 natural gas-fired 7.0 million Btu per hour dryer	N/A	N/A
SL1	One shop lathe (500 pounds per hour of rubber covered pad rolls)	SL 1C	One Cyclone (15 inch diameter)
SS1	One starch storage silo (22.5 tons per hour filling rate)	BF 1 BF 2	One Bagfilter (12 square feet of filter area) <i>in parallel with</i> One Bagfilter (12 square feet of filter area)
OP1	One blendomat (2600 pounds per hour of cotton fiber)	OP 1CA OP 1CB	One Paper Panel Filter (6.55 square feet of filter area) <i>in series with</i> One Rotary Drum Filter (46.5 square feet of filter area)
AC1/CARD1	One carding and drawing operation (2100 pounds per hour of cotton fiber)	CARD1-1C	One Rotary Drum Filter (545.3 square feet of surface area)
AC2	One spinning operation (2100 pounds per hour of cotton fiber)	AC2-1C	One Paper Filter (266.8 square feet of surface area)

Emission Source ID No.	Emission Source Description	Control Device ID No.	Control Device Description
AC3	One weaving operation (1870 pounds per hour of cotton yarn), consisting of : three weaving areas AC3, AC4, and AC5	AC3-1C	One Paper Filter (371.2 square feet of surface area) collecting from AC-3.
AC4		AC4-1C	One Rotary Drum Filter (834.9 square feet of surface area) collecting AC-4.
AC5		AC5-1C	One Rotary Drum Filter (545.3 square feet of surface area) collecting AC-5.
NAP1	One napping operation (2370 pounds per hour of cotton cloth), consisting of: two napping areas NAP1 and NAP2	NAP1-1C	One Rotary Drum Filter (483.3 square feet of surface area) collecting from NAP 1.
NAP2		NAP2-1C	One Rotary Drum Filter (142.1 square feet of surface area) collecting from NAP 2.
RP	Retention pond	N/A	N/A

SECTION 2 - SPECIFIC LIMITATIONS AND CONDITIONS

2.1- Emission Sources and Control Devices Specific Limitations and Conditions

The emission source(s) and associated air pollution control device(s) listed below are subject to the following specific terms, conditions, and limitations, including the monitoring, recordkeeping, and reporting requirements to which those requirements apply:

A. Natural gas/No. 6 fuel oil-fired boiler (ID No. B1)

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
particulate matter	0.33 pounds per million Btu heat input	15A NCAC 2D .0503
sulfur dioxide	2.3 pounds per million Btu heat input	15A NCAC 2D .0516
sulfur dioxide	See Subsection 2.2 (B)	15A NCAC 2Q .0317 (PSD avoidance)
visible emissions	20 percent opacity	15A NCAC 2D .0521
formaldehyde	See Subsection 2.2 (D) - State-enforceable Only	15A NCAC 2D .1100

1. 15A NCAC 2D .0503: PARTICULATES FROM FUEL BURNING INDIRECT HEAT EXCHANGERS

- a. Emissions of particulate matter from the combustion of natural gas or No. 6 fuel oil, that are discharged from this source into the atmosphere shall not exceed **0.33 pounds per million Btu heat input**. [15A NCAC 2D .0503 (a)]

Testing [15A NCAC 2D .0501(c)(3)]

- b. If emissions testing is required, the testing shall be performed in accordance General Condition JJ. If the results of this test are above the limit given in Section 2.1 A. 1. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0503.

Monitoring/Recordkeeping/Reporting Requirement 2Q .0508(f)]

- c. No monitoring/recordkeeping/reporting is required for particulate matter emissions from the firing of natural gas or fuel oil in this source.

2. 15A NCAC 2D .0516: SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

- a. Emissions of sulfur dioxide from this source shall not exceed 2.3 pounds per million Btu heat input. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard. [15A NCAC 2D .0516]

Testing [15A NCAC 2D .0501(c)(4)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ found in Section 3. If the results of this test are above the limit given in Section 2.1 A. 2. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0516.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. The maximum sulfur content of any oil received and burned in the boiler shall not exceed 2.1 percent by weight. [15A NCAC 2Q .0508(bb)]

- d. The Permittee shall monitor the sulfur content of the oil by using oil supplier certification per shipment received. The oil supplier certification shall be recorded on a quarterly basis and include the following information:
- i. the name of the oil supplier;
 - ii. the maximum sulfur content of the oil received during the quarter;
 - iii. the method used to determine the maximum sulfur content of the oil; and
 - iv. a certified statement signed by the responsible official that the records of oil supplier certification submitted represent all of the oil combusted during the reporting period.
- The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0516 if these records are not kept or if the results show an exceedance of the limit given in Section 2.1 A. 2. c. above.

Reporting [15A NCAC 2Q .0508(f)]

- f. The Permittee shall submit a summary report of the coal supplier certifications and calculations of the pounds of sulfur dioxide per million Btu heat content of the coal per total shipment post marked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

3. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from this source shall not be more than 20 percent opacity when averaged over a six-minute period. However, six-minute averaging periods may exceed 20 percent not more than once in any hour and not more than four times in any 24-hour period. In no event shall the six-minute average exceed 87 percent opacity. [15A NCAC 2D .0521 (d)]

Testing [15A NCAC 2D .0501(c)(8)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 A. 3.a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring [15A NCAC 2Q .0508(f)]

- c. To assure compliance, While firing No. 6 fuel oil once a day the Permittee shall observe the emission points of this source for any visible emissions above normal. The daily observation must be made for each day of the calendar year period to ensure compliance with this requirement. The Permittee shall be allowed three (3) days of absent observations per semi-annual period. If the emission sources is not firing No. 6 fuel oil, a record of this fact along with the corresponding date and time shall substitute for the daily observation. If visible emissions from this source are observed to be above normal, the Permittee shall either: (a) be deemed to be in noncompliance with 15A NCAC 2D .0521 or (b) demonstrate that the percent opacity from the emission points of the emission source in accordance with 15A NCAC 2D .0501(c)(8) is below the limit given in Section 2.1 A.3. a. above. If the demonstration in (b) above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521. No monitoring is required for visible emissions from the firing of natural gas in this source.

Recordkeeping [15A NCAC 2Q .0508(f)]

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
- i. the date and time of each recorded action;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.
- The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained. No recordkeeping is required for visible emissions from the firing of natural gas in this source.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified. No reporting is required for visible emissions from the firing of natural gas in this source.

B. Natural gas/No. 6 fuel oil-fired boiler (ID No. B2)

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
particulate matter	0.47 pounds per million Btu heat input	15A NCAC 2D .0503
sulfur dioxide	2.3 pounds per million Btu heat input	15A NCAC 2D .0516
sulfur dioxide	See Subsection 2.2 (B)	15A NCAC 2Q .0317 (PSD avoidance)
visible emissions	40 percent opacity	15A NCAC 2D .0521
formaldehyde	See Subsection 2.2 (D) - State-enforceable Only	15A NCAC 2D .1100

1. 15A NCAC 2D .0503: PARTICULATES FROM FUEL BURNING INDIRECT HEAT EXCHANGERS

- a. Emissions of particulate matter from the combustion of No. 6 fuel oil or natural gas that are discharged from this source into the atmosphere shall not exceed **0.47 pounds per million Btu heat input**. [15A NCAC 2D .0503 (a).]

Testing [15A NCAC 2D .0501(c)(3)]

- b. If emissions testing is required, the testing shall be performed in accordance General Condition JJ. If the results of this test are above the limit given in Section 2.1 B. 1. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0503.

Monitoring/Recordkeeping/Reporting Requirement 2Q .0508(f)]

- c. No monitoring/recordkeeping/reporting is required for particulate emissions from the firing of natural gas or fuel oil in this source.

2. 15A NCAC 2D .0516: SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

- a. Emissions of sulfur dioxide from this source shall not exceed **2.3 pounds per million Btu heat input**. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard. [15A NCAC 2D .0516]

Testing [15A NCAC 2D .0501(c)(4)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ found in Section 3. If the results of this test are above the limit given in Section 2.1 B. 2. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0516.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. The maximum sulfur content of any oil received and burned in the boiler shall not exceed 2.1 percent by weight. [15A NCAC 2Q .0508(bb)]

- d. The Permittee shall monitor the sulfur content of the oil by using oil supplier certification per shipment received. The oil supplier certification shall be recorded on a quarterly basis and include the following information:
 - i. the name of the oil supplier;
 - ii. the maximum sulfur content of the oil received during the quarter;
 - iii. the method used to determine the maximum sulfur content of the oil; and
 - iv. a certified statement signed by the responsible official that the records of oil supplier certification submitted represent all of the oil combusted during the reporting period.The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0516 if these records are not kept or if the results show an exceedance of the limit given in Section 2.1 B. 2. c. above.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of the oil supplier certifications by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

3. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from this source shall not be more than 40 percent opacity when averaged over a six-minute period except that six minute periods averaging not more than 90 percent opacity may occur not more than once in any hour nor more than four times in any 24-hour period. [15A NCAC 2D .0521(c)]

Testing [15A NCAC 2D .0501(c)(8)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 B. 3. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring [15A NCAC 2Q .0508(f)]

- c. To assure compliance, While firing No. 6 fuel oil once a day the Permittee shall observe the emission points of this source for any visible emissions above normal. The daily observation must be made for each day of the calendar year period to ensure compliance with this requirement. The Permittee shall be allowed three (3) days of absent observations per semi-annual period. If the emission sources is not firing No. 6 fuel oil, a record of this fact along with the corresponding date and time shall substitute for the daily observation. If visible emissions from this source are observed to be above normal, the Permittee shall either: (a) be deemed to be in noncompliance with 15A NCAC 2D .0521 or (b) demonstrate that the percent opacity from the emission points of the emission source in accordance with 15A NCAC 2D .0501(c)(8) is below the limit given in Section 2.1 B. 3. a. above. If the demonstration in (b) above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521. No monitoring is required for visible emissions from the firing of natural gas in this source.

Recordkeeping [15A NCAC 2Q .0508(f)]

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
 - i. the date and time of each recorded action;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained. No recordkeeping is required for visible emissions from the firing of natural gas in this source.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified. No reporting is required for visible emissions from the firing of natural gas in this source.

C. One natural gas-fired textile roller printer (ID No. PR3) and one natural gas-fired pigment range (ID No. PIG1)

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
particulate matter	$E = 4.10P^{0.67}$ where E = allowable emission rate in pounds per hour P = process weight rate in tons per hour	15A NCAC 2D .0515
sulfur dioxide	2.3 pounds per million Btu heat input	15A NCAC 2D .0516
volatile organic compounds	See Subsection 2.2 (A)	15A NCAC 2D .0958
volatile organic compounds	See Subsection 2.2 (C)	15A NCAC 2Q .0317 (PSD avoidance)
visible emissions	40 percent opacity	15A NCAC 2D .0521
formaldehyde, ammonia, and styrene	See Subsection 2.2 (D) - State-enforceable Only	15A NCAC 2D .1100

1. 15A NCAC 2D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

- a. Emissions of particulate matter from these sources shall not exceed an allowable emission rate as calculated by the following equation: [15A NCAC 2D .0515 (a)]

$$E = 4.10 \times P^{0.67} \quad \text{Where } E = \text{allowable emission rate in pounds per hour}$$

$$P = \text{process weight in tons per hour}$$

Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

Testing [15A NCAC 2D .0501 (c)(3)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 C. 1. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. The Permittee shall maintain production records which specify the types of materials and finishes processed and shall make these records available to a DAQ authorized representative upon request. The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if the production records are not maintained or the types of materials and finishes are not monitored.

Reporting [15A NCAC 2Q .0508 (f)]

- d. No reporting is required for emissions of particulate matter from these sources.

2. 15A NCAC 2D .0516: SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

- a. Emissions of sulfur dioxide from these sources shall not exceed 2.3 pounds per million Btu heat input. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard. [15A NCAC 2D .0516]

Testing [15A NCAC 2D .0501(c)(4)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ found in Section 3. If the results of this test are above the limit given in Section 2.1 C. 2. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0516.

Monitoring/Recordkeeping/Reporting [15A NCAC 2Q .0508 (f)]

- c. No monitoring/recordkeeping/reporting is required for sulfur dioxide emissions from the firing of natural gas in these sources.

3. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from these sources shall not be more than 40 percent opacity each when averaged over a six-minute period except that six minute periods averaging not more than 90 percent opacity may occur not more than once in any hour nor more than four times in any 24-hour period. [15A NCAC 2D .0521(c)]

Testing [15A NCAC 2D .0501(c)(8)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 D. 3. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring [15A NCAC 2Q .0508(f)]

- c. To assure compliance once a day the Permittee shall observe the emission points of these sources for any visible emissions above normal. The daily observation must be made for each day of the calendar year period to ensure compliance with this requirement. The Permittee shall be allowed three (3) days of absent observations per semi-annual period. If the emission sources is not operating, a record of this fact along with the corresponding date and time shall substitute for the daily observation. If visible emissions from the sources are observed to be above normal, the Permittee shall either: (a) be deemed to be in noncompliance with 15A NCAC 2D .0521 or (b) demonstrate that the percent opacity from the emission points of the emission sources in accordance with 15A NCAC 2D .0501(c)(8) is below the limit given in Section 2.1 D.3. a. above. If the demonstration in (b) above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

Recordkeeping [15A NCAC 2Q .0508(f)]

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
 - i. the date and time of each recorded action;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

D. One steam heated textile roller printer (ID No. PR1)

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
particulate matter	$E = 4.10P^{0.67}$ where E = allowable emission rate in pounds per hour P = process weight rate in tons per hour	15A NCAC 2D .0515
volatile organic compounds	See Subsection 2.2 (A)	15A NCAC 2D .0958
volatile organic compounds	See Subsection 2.2 (C)	15A NCAC 2Q .0317 (PSD avoidance)
visible emissions	40 percent opacity	15A NCAC 2D .0521
formaldehyde, ammonia, and styrene	See Subsection 2.2 (D) - State-enforceable Only	15A NCAC 2D .1100

1. 15A NCAC 2D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

- a. Emissions of particulate matter from this source shall not exceed an allowable emission rate as calculated by the following equation: [15A NCAC 2D .0515 (a)]

$$E = 4.10 \times P^{0.67} \quad \text{Where } E = \text{allowable emission rate in pounds per hour}$$

$$P = \text{process weight in tons per hour}$$

Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

Testing [15A NCAC 2D .0501 (c)(3)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 D. 1. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. The Permittee shall maintain production records which specify the types of materials and finishes processed and shall make these records available to a DAQ authorized representative upon request. The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if the production records are not maintained or the types of materials and finishes are not monitored.

Reporting [15A NCAC 2Q .0508(f)]

- d. No reporting is required for emission of particulate matter at this source.

2. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from this source shall not be more than 40 percent opacity each when averaged over a six-minute period except that six minute periods averaging not more than 90 percent opacity may occur not more than once in any hour nor more than four times in any 24-hour period. [15A NCAC 2D .0521(c)]

Testing [15A NCAC 2D .0501(c)(8)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 D. 3.a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring [15A NCAC 2Q .0508(f)]

- c. To assure compliance once a day the Permittee shall observe the emission points of this source for any visible emissions above normal. The daily observation must be made for each day of the calendar year period to ensure compliance with this requirement. The Permittee shall be allowed three (3) days of absent observations per semi-annual period. If the emission sources is not operating, a record of this fact along with the corresponding date and time shall substitute for the daily observation. If visible emissions from this source are observed to be above normal, the Permittee shall either: (a) be deemed to be in noncompliance with 15A NCAC 2D .0521 or (b) demonstrate that the percent opacity from the emission points of the emission source in accordance with 15A NCAC 2D .0501(c)(8) is below the limit given in Section 2.1 D. 3. a. above. If the demonstration in (b) above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

Recordkeeping [15A NCAC 2Q .0508(f)]

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
 - i. the date and time of each recorded action;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

E. One natural gas-fired textile roller printer (ID No. PR6), two natural gas-fired textile screen printers (ID Nos. PR4 and PR5), three natural gas-fired tenter frames (ID Nos. TEN1, TEN2, and TEN3), one natural gas-fired thermosol range (ID No. TR1), and one bleaching range with tenter frame (ID Nos. J-BOX, BL1, and TEN4)

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
particulate matter	$E = 4.10P^{0.67}$ where E = allowable emission rate in pounds per hour P = process weight rate in tons per hour	15A NCAC 2D .0515
sulfur dioxide	2.3 pounds per million Btu heat input	15A NCAC 2D .0516
volatile organic compounds	See Subsection 2.2 (A)	15A NCAC 2D .0958
volatile organic compounds	See Subsection 2.2 (C)	15A NCAC 2Q .0317 (PSD avoidance)
visible emissions	20 percent opacity	15A NCAC 2D .0521
formaldehyde, ammonia, and styrene	See Subsection 2.2 (D) - State-enforceable Only	15A NCAC 2D .1100

1. 15A NCAC 2D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

- a. Emissions of particulate matter from these sources shall not exceed an allowable emission rate as calculated by the following equation: [15A NCAC 2D .0515 (a)]

$$E = 4.10 \times P^{0.67} \quad \text{Where } E = \text{allowable emission rate in pounds per hour}$$

$$P = \text{process weight in tons per hour}$$

Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

Testing [15A NCAC 2D .0501 (c)(3)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 E. 1. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515.

Monitoring/Recordkeeping [15A NCAC 2Q .0508(f)]

- c. The Permittee shall maintain production records which specify the types of materials and finishes processed and shall make these records available to a DAQ authorized representative upon request. The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if the production records are not maintained or the types of materials and finishes are not monitored.

Reporting [15A NCAC 2Q .0508(f)]

- d. No reporting is required for emission of particulate matter at these sources.

2. 15A NCAC 2D .0516: SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

- a. Emissions of sulfur dioxide from these sources shall not exceed 2.3 pounds per million Btu heat input. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard. [15A NCAC 2D .0516]

Testing [15A NCAC 2D .0501(c)(4)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ found in Section 3. If the results of this test are above the limit given in Section 2.1 E. 1. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0516.

Monitoring/Recordkeeping/Reporting [15A NCAC 2Q .0508 (f)]

- c. No monitoring/recordkeeping/reporting is required for sulfur dioxide emissions from the firing of natural gas in these sources.

3. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from these sources shall not be more than 20 percent opacity each when averaged over a six-minute period except that six minute periods averaging not more than 87 percent opacity may occur not more than once in any hour nor more than four times in any 24-hour period. [15A NCAC 2D .0521(d)]

Testing [15A NCAC 2D .0501(c)(8)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 E. 3. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring [15A NCAC 2Q .0508(f)]

- c. To assure compliance once a day the Permittee shall observe the emission points of these sources for any visible emissions above normal. The daily observation must be made for each day of the calendar year period to ensure compliance with this requirement. The Permittee shall be allowed three (3) days of absent observations per semi-annual period. If the emission sources is not operating, a record of this fact along with the corresponding date and time shall substitute for the daily observation. If visible emissions from these sources are observed to be above normal, the Permittee shall either: (a) be deemed to be in noncompliance with 15A NCAC 2D .0521 or (b) demonstrate that the percent opacity from the emission points of the emission sources in accordance with 15A NCAC 2D .0501(c)(8) is below the limit given in Section 2.1 E. 3. a. above. If the demonstration in (b) above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

Recordkeeping [15A NCAC 2Q .0508(f)]

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
 - i. the date and time of each recorded action;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

F. One shop lathe (ID No. SL1) with one associated cyclone (ID No. SL1C), one starch storage silo (ID No. SS1) with two associated bagfilters (ID Nos. BF1 and BF2), and one blendomat operation (ID No. OP1) with one associated paper panel filter and one associated rotary drum filter (ID Nos. OP1CA and OP1CB)

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
particulate matter	$E = 4.10P^{0.67}$ where E = allowable emission rate in pounds per hour P = process weight rate in tons per hour	15A NCAC 2D .0515
visible emissions	20 percent opacity	15A NCAC 2D .0521

1. 15A NCAC 2D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

- a. Emissions of particulate matter from these sources shall not exceed an allowable emission rate as calculated by the following equation: [15A NCAC 2D .0515 (a)]

$$E = 4.10 \times P^{0.67} \quad \text{Where } E = \text{allowable emission rate in pounds per hour}$$

$$P = \text{process weight in tons per hour}$$

Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

Testing [15A NCAC 2D .0501 (c)(3)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 F. 1. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515.

Monitoring [15A NCAC 2Q .0508 (f)]

- c. Particulate matter emissions from the shop lathe shall be controlled by one cyclone. Particulate matter emissions from the starch storage silo shall be controlled by two bagfilters. Particulate matter emissions from the blendomat operation shall be controlled by one paper panel filter and one rotary drum filter. To ensure that optimum control efficiency of the control devices is maintained, the Permittee shall perform inspections and maintenance as recommended by the manufacturer. As a minimum, the inspection and maintenance program shall include:
 - i. monthly **external** inspection of the control devices and ductwork, and
 - ii. semi-annual **internal** inspection of the control devices to ensure structural integrity .
The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if the ductwork and control devices are not inspected and maintained.

Recording [15A NCAC 2Q .0508 (f)]

- d. The results of inspection and maintenance shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
 - i. the date and time of each recorded action;
 - ii. the results of each inspection;
 - iii. the results of any maintenance performed on the control devices; and
 - iv. any variance from manufacturer’s recommendations, if any, and corrections made.
The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if these records are not maintained.

Reporting [15A NCAC 2Q .0508 (f)]

- e. The Permittee shall submit the results of any maintenance performed on the control devices within 30 days of a written request by the DAQ.

- f. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

2. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from these sources shall not be more than 20 percent opacity each when averaged over a six-minute period except that six minute periods averaging not more than 87 percent opacity may occur not more than once in any hour nor more than four times in any 24-hour period. [15A NCAC 2D .0521(d)]

Testing [15A NCAC 2D .0501(c)(8)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 F. 2.a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring [15A NCAC 2Q .0508(f)]

- c. To assure compliance, once a month the Permittee shall observe the emission points of these sources for any visible emissions above normal. The Permittee shall establish "normal" for the source in the first 30 days following the effective date of permit. If visible emissions from these sources are observed to be above normal, the Permittee shall either: (a) be deemed to be in noncompliance with 15A NCAC 2D .0521 or (b) demonstrate that the percent opacity from the emission points of the emission sources in accordance with 15A NCAC 2D .0501(c)(8) is below the limit given in Section 2.1 F. 2. a. above. If the demonstration in (b) above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

Recordkeeping [15A NCAC 2Q .0508(f)]

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
 - i. the date and time of each recorded action;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

G. One carding and drawing operation (ID No. AC1/CARD1) with one associated rotary drum filter (ID No. CARD1-1C), one spinning operation (ID No. AC2) with one associated paper filter (ID No. AC2-1C), one weaving operation (ID Nos. AC3, AC4, and AC5) with one associated paper filter and two rotary drum filters (ID Nos. AC3-1C, AC4-1C, and AC5-1C), and one napping operation (ID Nos. NAP1 and NAP2) with two associated rotary drum filters (ID Nos. NAP1-1C and NAP2-1C)

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
particulate matter	$E = 4.10P^{0.67}$ where E = allowable emission rate in pounds per hour P = process weight rate in tons per hour	15A NCAC 2D .0515
visible emissions	40 percent opacity	15A NCAC 2D .0521

1. 15A NCAC 2D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

- a. Emissions of particulate matter from these sources shall not exceed an allowable emission rate as calculated by the following equation: [15A NCAC 2D .0515 (a)]

$$E = 4.10 \times P^{0.67} \quad \text{Where } E = \text{allowable emission rate in pounds per hour}$$

$$P = \text{process weight in tons per hour}$$

Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

Testing [15A NCAC 2D .0501 (c)(3)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 G. 1. a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515.

Monitoring [15A NCAC 2Q .0508 (f)]

- c. Particulate matter emissions from the carding and drawing operation shall be controlled by one rotary drum filter. Particulate matter emissions from the spinning operation shall be controlled by one paper filter. Particulate matter emissions from the weaving operation shall be controlled by one paper panel filter and two rotary drum filters. Particulate matter emissions from the napping operation shall be controlled by two rotary drum filters. To ensure that optimum control efficiency of the control devices is maintained, the Permittee shall perform inspections and maintenance as recommended by the manufacturer. As a minimum, the inspection and maintenance program shall include:

- i. monthly **external** inspection of the control devices and ductwork, and
- ii. semi-annual **internal** inspection of the control devices to ensure structural integrity .

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if the ductwork and control devices are not inspected and maintained.

Recordkeeping [15A NCAC 2Q .0508 (f)]

- d. The results of inspection and maintenance shall be maintained in a log book (written or electronic form) on site and made available to an authorized representative upon request. The log book shall record the following:
- i. date and time of actions recorded;
 - ii. the results of each monthly inspection;
 - iii. the results of any maintenance performed on the control devices; and
 - iv. any variance from manufacturer's recommendations, if any, and corrections made.
- The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0515 if these records are not maintained.

Reporting [15A NCAC 2Q .0508 (f)]

- e. The Permittee shall submit the results of any maintenance performed on the control devices within 30 days of a written request by the DAQ.
- f. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

2. 15A NCAC 2D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from these sources shall not be more than 40 percent opacity each when averaged over a six-minute period except that six minute periods averaging not more than 90 percent opacity may occur not more than once in any hour nor more than four times in any 24-hour period. [15A NCAC 2D .0521(c)]

Testing [15A NCAC 2D .0501(c)(8)]

- b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 G. 2.a. above, the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521.

Monitoring [15A NCAC 2Q .0508(f)]

- c. To assure compliance, once a month the Permittee shall observe the emission points of these sources for any visible emissions above normal. The Permittee shall establish "normal" for the source in the first 30 days following the effective date of permit. If visible emissions from these sources are observed to be above normal, the Permittee shall either: (a) be deemed to be in noncompliance with 15A NCAC 2D .0521 or (b) demonstrate that the percent opacity from the emission points of the emission sources in accordance with 15A NCAC 2D .0501(c)(8) is below the limit given in Section 2.1 G. 2. a. above. If the demonstration in (b) above cannot be made, the Permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0521.

Recordkeeping [15A NCAC 2Q .0508(f)]

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
- i. the date and time of each recorded action;
 - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
 - iii. the results of any corrective actions performed.
- The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0521 if these records are not maintained.

Reporting [15A NCAC 2Q .0508(f)]

- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

2.2- Multiple Emission Source(s) Specific Limitations and Conditions

- A. one steam heated textile roller printer (ID No. PR1),
one natural gas-fired textile roller printer (ID No. PR3),
one natural gas-fired pigment range (ID No. PIG1),
one natural gas-fired textile roller printer (ID No. PR6),
two natural gas-fired textile screen printers (ID Nos. PR4 and PR5),
three natural gas-fired tenter frames (ID Nos. TEN1, TEN2, and TEN3),
one natural gas-fired thermosol range (ID No. TR1),
one bleach range and natural gas-fired finishing range (ID Nos. J-BOX, BL1, and TEN4),
and
one steam heated cotton dye range (ID No. CR1)**

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
volatile organic compound	work practice standards	15A NCAC 2D .0958

1. 15A NCAC 2D .0958: WORK PRACTICES FOR SOURCES OF VOLATILE ORGANIC COMPOUNDS

- a. Pursuant to 15A NCAC 2D .0958 and 2D .0902, for all sources that use volatile organic compounds (VOC) as solvents, carriers, material processing media, or industrial chemical reactants, or in similar uses that mix, blend, or manufacture volatile organic compounds, or emit volatile organic compounds as a product of chemical reactions, and whose emissions of VOC are greater than 15 pounds per day; the Permittee shall:
- (1) store all material, including waste material, containing volatile organic compounds in tanks or in containers covered with a tightly fitting lid that is free of cracks, holes, or other defects, when not in use,
 - (2) clean up spills of volatile organic compounds as soon as possible following proper safety procedures,
 - (3) store wipe rags containing volatile organic compounds in closed containers,
 - (4) not clean sponges, fabric, wood, paper products, and other absorbent materials with volatile organic compounds,
 - (5) transfer solvents containing volatile organic compounds used to clean supply lines and other coating equipment into closable containers and close such containers immediately after each use, or transfer such solvents to closed tanks, or to a treatment facility regulated under section 402 of the Clean Water Act,
 - (6) clean mixing, blending, and manufacturing vats and containers containing volatile organic compounds by adding cleaning solvent and close the vat or container before agitating the cleaning solvent. The spent cleaning solvent shall then be transferred into a closed container, a closed tank or a treatment facility regulated under section 402 of the Clean Water Act. [15A NCAC 2D .0958(c)]
- b. When cleaning parts with a solvent containing a volatile organic compound, the Permittee shall:
- (1) flush parts in the freeboard area,
 - (2) take precautions to reduce the pooling of solvent on and in the parts,
 - (3) tilt or rotate parts to drain solvent and allow a minimum of 15 seconds for drying or until all dripping has stopped, whichever is longer,
 - (4) not fill cleaning machines above the fill line,
 - (5) not agitate solvent to the point of causing splashing. [15A NCAC 2D .0958(d)]

Monitoring

- c. To assure compliance with paragraphs (a) and (b) above, the Permittee shall, at a minimum, perform a visual inspection once per month of all operations and processes utilizing volatile organic compounds and shall immediately initiate any corrective actions required to meet the requirements of paragraphs (a) and (b) above. The inspections shall be conducted during normal operations. If the required inspections are not conducted the permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0958.

Recordkeeping

- d. The results of the inspections shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
 - i. the date and time of each inspection; and
 - ii. the results of each inspection noting whether or not noncompliant conditions were observed and whether or not corrective actions were taken to restore compliance.
 If the required records are not maintained the permittee shall be deemed to be in noncompliance with 15A NCAC 2D .0958.

Reporting

- e. The Permittee shall submit a summary report of the observations by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

B. Two natural gas/No. 6 fuel oil-fired boilers (ID Nos. B1 and B2)

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
sulfur dioxide	250 tons per year	15A NCAC 2Q .0317 (PSD avoidance)

**1. 15A NCAC 2Q. 0317: AVOIDANCE CONDITIONS
AVOIDANCE FOR 15A NCAC 2D. 0530: PREVENTION OF SIGNIFICANT DETERIORATION**

- a. In order to avoid applicability of 2D .0530(g), the above emission sources shall discharge into the atmosphere less than 250 tons of sulfur dioxide per consecutive twelve month period. [15A NCAC 2D .0530]

Testing [15A NCAC 2Q .0501 (c)(4)]

- b. If emissions testing is required, the Permittee shall perform such testing in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.2 B. 1. a., the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0530.

Monitoring/Recordkeeping [15A NCAC 2Q .0508 (f)]

- c. The use of fuel in both boilers shall be limited such that sulfur dioxide emissions, as calculated by the following formula, shall not exceed 250 tons for any twelve month period:

$$\text{Total actual pounds sulfur dioxide emitted} = X \times 0.6 \text{ pound sulfur dioxide/million cubic feet} + Z \times 157 \text{ pound sulfur dioxide/1000 gallons} \times S$$

Where: X is the amount of natural gas used in both boilers in cubic feet
Z is the amount of No. 6 fuel oil used in both boilers in gallons
S is the percent sulfur in the No. 6 fuel oil

Monthly records shall be kept in a log book (written or electronic format) of the amount of each fuel combusted and the percent sulfur in each shipment of oil received.

- d. Calculations shall be made monthly using the above formula and recorded in the log book. Calculation of the consecutive twelve month periods shall begin upon issuance of this permit.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0530 if the above records are not kept or if the sulfur dioxide emissions exceed the limit in Section 2.2 B. 1. a.

Reporting [15A NCAC 2Q .0508 (f)]

- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities by January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. The report shall contain the following:
 - i. The monthly sulfur dioxide emissions for the previous fourteen months. The emissions must be calculated for each of the twelve month periods over the previous fourteen months,
 - ii. The monthly quantities of natural gas and No. 6 fuel oil consumed for the previous fourteen months, and
 - iii. All instances of deviations from the requirements of this permit must be clearly identified.

**C. one steam heated textile roller printer (ID No. PR1),
 one natural gas-fired textile roller printer (ID No. PR3),
 one natural gas-fired pigment range (ID No. PIG1),
 one natural gas-fired textile roller printer (ID No. PR6),
 two natural gas-fired textile screen printers (ID Nos. PR4 and PR5),
 three natural gas-fired tenter frames (ID Nos. TEN1, TEN2, and TEN3),
 one natural gas-fired thermosol range (ID No. TR1), and
 one bleach range and natural gas-fired finishing range (ID Nos. J-BOX, BL1, and TEN4)**

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
volatile organic compound	250 tons per year	15A NCAC 2Q .0317 (PSD avoidance)

1. 15A NCAC 2D. 0530: PREVENTION OF SIGNIFICANT DETERIORATION

- a. In order to avoid applicability of 2D .0530(g), the above emission sources shall discharge into the atmosphere less than 250 tons of volatile organic compounds per consecutive twelve month period. [15A NCAC 2D .0530]

Testing [15A NCAC 2Q .0501 (c)(4)]

- b. If emissions testing is required, the Permittee shall perform such testing in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.2 C. 1. a., the Permittee shall be deemed in noncompliance with 15A NCAC 2D .0530.

Monitoring/Recordkeeping [15A NCAC 2Q .0508 (f)]

- c. Monthly records shall be kept in a log book (written or electronic format) of the amount of each VOC-containing material consumed. Calculations of VOC emissions per month shall be made at the end of each month. VOC emissions shall be determined by multiplying the total amount of each type of VOC-containing material consumed during the month by the VOC content of the material.
- d. Calculation of the consecutive twelve month periods shall begin upon issuance of this permit. Calculations and the total amount of VOC volatile organic compound emissions shall be recorded monthly in a log book.

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .0530 if the above records are not kept or if the

sulfur dioxide emissions exceed the limit in Section 2.2 C. 1. a.

Reporting [15A NCAC 2Q .0508 (f)]

- e. The Permittee shall submit a summary report of monitoring and recordkeeping activities within 30 days after each calendar year quarter, due and postmarked on or before January 30 of each calendar year for the preceding three-month period between October and December, April 30 of each calendar year for the preceding three-month period between January and March, July 30 of each calendar year for the preceding three-month period between April and June, and October 30 for the calendar year for the preceding three-month period between July and September. The report shall contain the following:
 - i. The monthly volatile organic compound emissions for the previous fourteen months. The emissions must be calculated for each of the twelve month periods over the previous fourteen months, and
 - ii. All instances of deviations from the requirements of this permit must be clearly identified.

STATE ONLY REQUIREMENT:

D. TOXIC AIR POLLUTANT EMISSIONS LIMITATION AND REPORTING

REQUIREMENT - Pursuant to 15A NCAC 2D .1100 and in accordance with the approved application for an air toxic compliance demonstration, the following permit limit shall not be exceeded:

EMISSION SOURCE(S)	TOXIC AIR POLLUTANT(S)	EMISSION LIMIT(S)
Printer (ID No. PR1)	Ammonia Formaldehyde Styrene	3.36 pounds per hour 0.084 pounds per hour 1.24 pounds per hour
Tenter frame (ID No. TEN1)	Ammonia Formaldehyde Methyl isobutyl ketone Styrene	0.228 pounds per hour 0.104 pounds per hour 6.32 pounds per hour 0.21 pounds per hour
Tenter frame (ID No. TEN2)	Ammonia Formaldehyde Methyl isobutyl ketone Styrene	0.30 pounds per hour 0.128 pounds per hour 6.32 pounds per hour 0.21 pounds per hour
Tenter frame (ID No. TEN3)	Ammonia Formaldehyde Methyl isobutyl ketone Styrene	0.228 pounds per hour 0.104 pounds per hour 6.32 pounds per hour 0.21 pounds per hour
Tenter frame (ID No. TEN4)	Ammonia	0.004 pounds per hour
Boiler (ID No. B1)	Formaldehyde	0.0204 pounds per hour
Boiler (ID No. B2)	Formaldehyde	0.0007 pounds per hour
Printer (ID No. PR3)	Ammonia Formaldehyde Styrene	3.36 pounds per hour 0.084 pounds per hour 1.24 pounds per hour
Printer (ID No. PR4)	Ammonia Formaldehyde Styrene	2.86 pounds per hour 0.084 pounds per hour 1.24 pounds per hour
Printer (ID No. PR5)	Ammonia Formaldehyde Styrene	2.86 pounds per hour 0.084 pounds per hour 1.24 pounds per hour
Printer (ID No. PR6)	Ammonia Formaldehyde Styrene	3.36 pounds per hour 0.086 pounds per hour 1.24 pounds per hour
Pigment range (ID No. PIG1)	Formaldehyde	0.0008 pounds per hour
Thermosol range (ID No. TR1)	Ammonia Formaldehyde	1.12 pounds per hour 0.002 pounds per hour
Retention pond (ID No. RP)	Ammonia Formaldehyde	0.0012 pounds per hour 0.0016 pounds per hour

1. To ensure compliance with the above limits, the following restrictions shall apply:
 - i. The input rate of ammonia to each roller printer (ID Nos. PR1, PR3, and PR6) shall not exceed 3.35 pounds per hour,
 - ii. The input rate of ammonia to each screen printer (ID Nos. PR4 and PR5) shall not exceed 2.85 pounds per hour,

- iii. The input rate of formaldehyde to each tenter frame (ID Nos. TEN1 and TEN3) shall not exceed 0.104 pounds per hour, and
 - iv. The input rate of formaldehyde to the tenter frame (ID No. TEN2) shall not exceed 0.126 pounds per hour.
2. The Permittee shall keep daily records in a logbook of the following:
- i. The maximum hourly rate of ammonia input to each printer (ID Nos. PR1, PR3, PR4, PR5, and PR6) for each day of production, and
 - ii. The maximum hourly rate of formaldehyde input to each tenter frame (ID Nos. TEN1, TEN2, and TEN3) for each day of production.
3. For compliance purposes, within thirty (30) days after each calendar year quarter the following shall be reported to the Regional Supervisor, Division of Air Quality:
- i. The maximum hourly rate of ammonia input to each printer (ID Nos. PR1, PR3, PR4, PR5, and PR6) for each day of production, and
 - ii. The maximum hourly rate of formaldehyde input to each tenter frame (ID Nos. TEN1, TEN2, and TEN3) for each day of production.

E. All emission sources

The following table provides a summary of limits and standards for the emission source(s) describe above:

Regulated Pollutant	Limits/Standards	Applicable Regulation
odors	odorous emissions must be controlled; State-enforceable only	15A NCAC 2D .1806

STATE-ONLY REQUIREMENT: ODOR REQUIREMENTS

- 1. 15A NCAC 2D .1806: CONTROL AND PROHIBITION OF ODOROUS EMISSIONS**
- a. the Permittee shall not operate the facility without implementing management practices or installing and operating odor control equipment sufficient to prevent odorous emissions from the facility from causing or contributing to objectionable odors beyond the facility's boundary.

SECTION 3 - GENERAL CONDITIONS

This section describes terms and conditions applicable to this Title V facility. All references to the “permit” in this section apply only to Part I of the permit.

- A. **General Provisions** [NCGS 143-215 and 15A NCAC 2Q .0508(i)(16)]
- 1. Terms not otherwise defined in this permit shall have the meaning assigned to such terms as defined in 15A NCAC 2D and 2Q.
 - 2. The terms, conditions, requirements, limitations, and restrictions set forth in this permit are binding and enforceable pursuant to NCGS 143-215.114A and 143-215.114B, including assessment of civil and/or criminal penalties. Any unauthorized deviation from the conditions of this permit may constitute grounds for revocation and/or enforcement action by the DAQ.
 - 3. This permit is not a waiver of or approval of any other Department permits that may be required for other aspects of the facility which are not addressed in this permit.

4. This permit does not relieve the Permittee from liability for harm or injury to human health or welfare, animal or plant life, or property caused by the construction or operation of this permitted facility, or from penalties therefore, nor does it allow the Permittee to cause pollution in contravention of state laws or rules, unless specifically authorized by an order from the North Carolina Environmental Management Commission.
5. Except as identified as state-only requirements in this permit, all terms and conditions contained herein shall be enforceable by the DAQ, the EPA, and citizens of the United States as defined in the Federal Clean Air Act.
6. Any stationary source of air pollution shall not be operated, maintained, or modified without the appropriate and valid permits issued by the DAQ, unless the source is exempted by rule. The DAQ may issue a permit only after it receives reasonable assurance that the installation will not cause air pollution in violation of any of the applicable requirements. A permitted installation may only be operated, maintained, constructed, expanded, or modified in a manner that is consistent with the terms of this permit.

B. **Permit Availability** [15A NCAC 2Q .0507(k) and .0508(i)(9)(B)]

The Permittee shall have available at the facility a copy of this permit and shall retain for the duration of the permit term one complete copy of the application and any information submitted in support of the application package. The permit and application shall be made available to an authorized representative of Department of Environment and Natural Resources upon request.

C. **Severability Clause** [15A NCAC 2Q .0508(i)(2)]

In the event of an administrative challenge to a final and binding permit in which a condition is held to be invalid, the provisions in this permit are severable so that all requirements contained in the permit, except those held to be invalid, shall remain valid and must be complied with.

D. **Submissions** [15A NCAC 2Q .0507(e) and 2Q .0508(i)(16)]

Except as otherwise specified herein, two copies of all documents, reports, test data, monitoring data, notifications, request for renewal, and any other information required by this permit shall be submitted to the appropriate Regional Office. Refer to the Regional Office address on the cover page of this permit. For continuous emissions monitoring systems (CEMS) reports, continuous opacity monitoring systems (COMS) reports, quality assurance (QA)/quality control (QC) reports, acid rain CEM certification reports, and NOx budget CEM certification reports, one copy shall be sent to the appropriate Regional Office and one copy shall be sent to:

Supervisor, Stationary Source Compliance
North Carolina Division of Air Quality
1641 Mail Service Center
Raleigh, NC 27699-1641

E. **Duty to Comply** [15A NCAC 2Q .0508(i)(2)]

The Permittee shall comply with all terms, conditions, requirements, limitations and restrictions set forth in this permit. Noncompliance with any permit condition except conditions identified as state-only requirements constitutes a violation of the Federal Clean Air Act. Noncompliance with any permit condition is grounds for enforcement action, for permit termination, revocation and reissuance, or modification, or for denial of a permit renewal application.

F. **Circumvention** - STATE ENFORCEABLE ONLY

The facility shall be properly operated and maintained at all times in a manner that will effect an overall reduction in air pollution. Unless otherwise specified by this permit, no emission source may be operated without the concurrent operation of its associated air pollution control device(s) and appurtenances.

G. **Permit Modifications**

1. Administrative Permit Amendments [15A NCAC 2Q .0514]

The Permittee shall submit an application for an administrative permit amendment in accordance with 15A NCAC 2Q .0514.

2. Transfer in Ownership or Operation and Application Submittal Content [15A NCAC 2Q .0524 and 2Q .0505]

The Permittee shall submit an application for an ownership change in accordance with 15A NCAC 2Q.0524 and 2Q .0505.

3. Minor Permit Modifications [15A NCAC 2Q .0515]

The Permittee shall submit an application for a minor permit modification in accordance with 15A NCAC 2Q .0515.

4. Significant Permit Modifications [15A NCAC 2Q .0516]

The Permittee shall submit an application for a significant permit modification in accordance with 15A NCAC 2Q .0516.

5. Reopening for Cause [15A NCAC 2Q .0517]

The Permittee shall submit an application for reopening for cause in accordance with 15A NCAC 2Q .0517.

H. **Changes Not Requiring Permit Modifications**

1. Section 502(b)(10) Changes [15A NCAC 2Q .0523(a)]

a. "Section 502(b)(10) changes" means changes that contravene an express permit term or condition. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), recordkeeping, reporting, or compliance certification requirements.

b. The Permittee may make Section 502(b)(10) changes without having the permit revised if:

i. the changes are not a modification under Title I of the Federal Clean Air Act;

ii. the changes do not cause the allowable emissions under the permit to be exceeded;

iii. the Permittee notifies the Director and EPA with written notification at least seven days before the change is made; and

iv. the Permittee shall attach the notice to the relevant permit.

c. The written notification shall include:

i. a description of the change;

ii. the date on which the change will occur;

iii. any change in emissions; and

iv. any permit term or condition that is no longer applicable as a result of the change.

d. Section 502(b)(10) changes shall be made in the permit the next time that the permit is revised or renewed, whichever comes first.

2. Off Permit Changes [15A NCAC 2Q .0523(b)]

The Permittee may make changes in the operation or emissions without revising the permit if:

a. the change affects only insignificant activities and the activities remain insignificant after the change; or

b. the change is not covered under any applicable requirement.

3. Emissions Trading [15A NCAC 2Q .0523(c)]

To the extent that emissions trading is allowed under 15A NCAC 2D, including subsequently adopted maximum achievable control technology standards, emissions trading shall be allowed without permit revision pursuant to 15A NCAC 2Q .0523(c).

I.A. Reporting Requirements for Excess Emissions and Permit Deviations

[15A NCAC 2D .0535(f) and 2Q .0508(f)(2)]

“Excess Emissions” - means an emission rate that exceeds any applicable emission limitation or standard allowed by any rule in Sections .0500, .0900, .1200, or .1400 of Subchapter 2D; or by a permit condition; or that exceeds an emission limit established in a permit issued under 15A NCAC 2Q .0700. (*Note: Definitions of excess emissions under 2D .1110 and 2D .1111 shall apply where defined by rule.*)

“Deviations” - for the purposes of this condition, any action or condition not in accordance with the terms and conditions of this permit including those attributable to upset conditions as well as excess emissions as defined above lasting less than four hours.

Excess Emissions

1. If a source is required to report excess emissions under NSPS (15A NCAC 2D .0524), NESHAPS (15A NCAC 2D .1110 or .1111), or the operating permit provides for periodic (e.g., quarterly) reporting of excess emissions, reporting shall be performed as prescribed therein.
2. If the source is not subject to NSPS (15A NCAC 2D .0524), NESHAPS (15A NCAC 2D .1110 or .1111), or these rules do NOT define "excess emissions," the Permittee shall report excess emissions in accordance with 15A NCAC 2D .0535 as follows:
 - a. Pursuant to 15A NCAC 2D .0535, if excess emissions last for more than four hours resulting from a malfunction, a breakdown of process or control equipment, or any other abnormal condition, the owner or operator shall:
 - i. notify the Regional Supervisor or Director of any such occurrence by 9:00 a.m. Eastern Time of the Division's next business day of becoming aware of the occurrence and provide:
 - name and location of the facility;
 - nature and cause of the malfunction or breakdown;
 - time when the malfunction or breakdown is first observed;
 - expected duration; and
 - estimated rate of emissions;
 - ii. notify the Regional Supervisor or Director immediately when corrective measures have been accomplished; and
 - iii. submit to the Regional Supervisor or Director within 15 days a written report as described in 15A NCAC 2D .0535(f)(3).

Permit Deviations

3. Pursuant to 15A NCAC 2Q .0508(f)(2), the Permittee shall report deviations from permit requirements (terms and conditions) as follows:
 - a. Notify the Regional Supervisor or Director of all other deviations from permit requirements not covered under 15A NCAC 2D .0535 quarterly. A written report to the Regional Supervisor shall include the probable cause of such deviation and any corrective actions or preventative actions taken. The responsible official shall certify all deviations from permit requirements.

I.B. Other Requirements under 15A NCAC 2D .0535

The Permittee shall comply with all other applicable requirements contained in 15A NCAC 2D .0535, including 15A NCAC 2D .0535(c) as follows:

1. Any excess emissions that do not occur during start-up and shut-down shall be considered a violation of the appropriate rule unless the owner or operator of the sources demonstrates to the Director, that the excess emissions are a result of a malfunction. The Director shall consider, along with any other pertinent information, the criteria contained in 15A NCAC 2D .0535(c)(1) through (7).
2. 15A NCAC 2D .0535(g). Excess emissions during start-up and shut-down shall be considered a violation of the appropriate rule if the owner or operator cannot demonstrate that excess emissions are unavoidable.

J. **Emergency Provisions** [40 CFR 70.6(g)]

The Permittee shall be subject to the following provisions with respect to emergencies:

1. An emergency means any situation arising from sudden and reasonably unforeseeable events beyond the control of the facility, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventive maintenance, careless or improper operation, or operator error.
2. An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions specified in 3. below are met.
3. The affirmative defense of emergency shall be demonstrated through properly signed contemporaneous operating logs or other relevant evidence that include information as follows:
 - a. an emergency occurred and the Permittee can identify the cause(s) of the emergency;
 - b. the permitted facility was at the time being properly operated;
 - c. during the period of the emergency the Permittee took all reasonable steps to minimize levels of emissions that exceeded the standards or other requirements in the permit; and
 - d. the Permittee submitted notice of the emergency to the DAQ within two working days of the time when emission limitations were exceeded due to the emergency. This notice must contain a description of the emergency, steps taken to mitigate emissions, and corrective actions taken.
4. In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
5. This provision is in addition to any emergency or upset provision contained in any applicable requirement specified elsewhere herein.

K. **Permit Renewal** [15A NCAC 2Q .0508(e) and 2Q .0513(b)]

This permit is issued for a fixed term of five years for facilities subject to Title IV requirements and for a term not to exceed five years in the case of all other facilities. This permit shall expire at the end of its term. Permit expiration terminates the facility's right to operate unless a complete renewal application is submitted at least nine months before the date of permit expiration. If the Permittee or applicant has complied with 15A NCAC 2Q .0512(b)(1), this permit shall not expire until the renewal permit has been issued or denied. All terms and conditions of this permit shall remain in effect until the renewal permit has been issued or denied.

L. **Need to Halt or Reduce Activity Not a Defense** [15A NCAC 2Q .0508(i)(4)]

It shall not be a defense for a Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

M. **Duty to Provide Information (submittal of information)** [15A NCAC 2Q .0508(i)(9)]

1. The Permittee shall furnish to the DAQ, in a timely manner, any reasonable information that the Director may request in **writing** to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit.
2. The Permittee shall furnish the DAQ copies of records required to be kept by the permit when such copies are requested by the Director. For information claimed to be confidential, the Permittee may furnish such records directly to the EPA upon request along with a claim of confidentiality.

N. **Duty to Supplement** [15A NCAC 2Q .0507(f)]

The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to the DAQ. The Permittee shall also provide additional information as necessary to address any requirement that becomes applicable to the facility after the date a complete permit application was submitted but prior to the release of the draft permit.

O. **Retention of Records** [15A NCAC 2Q .0508(f) and 2Q .0508 (l)]

The Permittee shall retain records of all required monitoring data and supporting information for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring information, and copies of all reports required by the permit. These records shall be maintained in a form suitable and readily available for expeditious inspection and review. Any records required by the conditions of this permit shall be kept on site and made available to DAQ personnel for inspection upon request.

P. **Compliance Certification** [15A NCAC 2Q .0508(n)]

The Permittee shall submit to the DAQ and the EPA (Air and EPCRA Enforcement Branch, EPA, Region 4, 61 Forsyth Street, Atlanta, GA 30303) postmarked on or before March 1 a compliance certification (for the preceding calendar year) by a responsible official with all federally-enforceable terms and conditions in the permit, including emissions limitations, standards, or work practices. It shall be the responsibility of the current owner to submit a compliance certification for the entire year regardless of who owned the facility during the year. The compliance certification shall comply with additional requirements as may be specified under Sections 114(a)(3) or 504(b) of the Federal Clean Air Act. The compliance certification shall specify:

1. the identification of each term or condition of the permit that is the basis of the certification;
2. the compliance status (with the terms and conditions of the permit for the period covered by the certification);
3. whether compliance was continuous or intermittent; and
4. the method(s) used for determining the compliance status of the source during the certification period.

Q. **Certification by Responsible Official** [15A NCAC 2Q .0520]

A responsible official shall certify the truth, accuracy, and completeness of any application form, report, or compliance certification required by this permit. All certifications shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

R. **Permit Shield for Applicable Requirements** [15A NCAC 2Q .0512]

1. Compliance with the terms and conditions of this permit shall be deemed compliance with applicable requirements, where such applicable requirements are included and specifically identified in the permit as of the date of permit issuance.
2. A permit shield shall not alter or affect:
 - a. the power of the Commission, Secretary of the Department, or Governor under NCGS 143-215.3(a)(12), or EPA under Section 303 of the Federal Clean Air Act;
 - b. the liability of an owner or operator of a facility for any violation of applicable requirements prior to the effective date of the permit or at the time of permit issuance;
 - c. the applicable requirements under Title IV; or
 - d. the ability of the Director or the EPA under Section 114 of the Federal Clean Air Act to obtain information to determine compliance of the facility with its permit.
3. A permit shield does not apply to any change made at a facility that does not require a permit or permit revision made under 15A NCAC 2Q .0523.
4. A permit shield does not extend to minor permit modifications made under 15A NCAC 2Q .0515.

S. **Termination, Modification, and Revocation of the Permit** [15A NCAC 2Q .0519]

The Director may terminate, modify, or revoke and reissue this permit if:

1. the information contained in the application or presented in support thereof is determined to be incorrect;
2. the conditions under which the permit or permit renewal was granted have changed;
3. violations of conditions contained in the permit have occurred;
4. the EPA requests that the permit be revoked under 40 CFR 70.7(g) or 70.8(d); or
5. the Director finds that termination, modification, or revocation and reissuance of the permit is necessary to carry out the purpose of NCGS Chapter 143, Article 21B.

T. **Insignificant Activities** [15A NCAC 2Q .0503]

Because an emission source or activity is insignificant does not mean that the emission source or activity is exempted from any applicable requirement or that the owner or operator of the source is exempted from demonstrating compliance with any applicable requirement. The Permittee shall have available at the facility at all times and made available to an authorized representative upon request, documentation, including calculations, if necessary, to demonstrate that an emission source or activity is insignificant.

U. **Property Rights** [15A NCAC 2Q .0508(i)(8)]

This permit does not convey any property rights in either real or personal property or any exclusive privileges.

V. **Inspection and Entry** [15A NCAC 2Q .0508(l) and NCGS 143-215.3(a)(2)]

1. Upon presentation of credentials and other documents as may be required by law, the Permittee shall allow the DAQ, or an authorized representative, to perform the following:
 - a. enter the Permittee's premises where the permitted facility is located or emissions-related activity is conducted, or where records are kept under the conditions of the permit;
 - b. have access to and copy, at reasonable times, any records that are required to be kept under the conditions of the permit;
 - c. inspect at reasonable times and using reasonable safety practices any source, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - d. sample or monitor substances or parameters, using reasonable safety practices, for the purpose of assuring compliance with the permit or applicable requirements at reasonable times.

Nothing in this condition shall limit the ability of the EPA to inspect or enter the premises of the Permittee under Section 114 or other provisions of the Federal Clean Air Act.

2. No person shall refuse entry or access to any authorized representative of the DAQ who requests entry for purposes of inspection, and who presents appropriate credentials, nor shall any person obstruct, hamper, or interfere with any such authorized representative while in the process of carrying out his official duties. Refusal of entry or access may constitute grounds for permit revocation and assessment of civil penalties.

W. **Annual Fee Payment** [15A NCAC 2Q .0508(i)(10)]

1. The Permittee shall pay all fees in accordance with 15A NCAC 2Q .0200.
2. Payment of fees may be by check or money order made payable to the N.C. Department of Environment and Natural Resources. Annual permit fee payments shall refer to the permit number.
3. If, within 30 days after being billed, the Permittee fails to pay an annual fee, the Director may initiate action to terminate the permit under 15A NCAC 2Q .0519.

X. **Annual Emission Inventory Requirements** [15A NCAC 2Q .0207]

The Permittee shall report by **June 30 of each year** the actual emissions of each air pollutant listed in 15A NCAC 2Q .0207(a) from each emission source within the facility during the previous calendar year. The report shall be in or on such form as may be established by the Director. The accuracy of the report shall be certified by a responsible official of the facility.

Y. **Confidential Information** [15A NCAC 2Q .0107 and 2Q. 0508(i)(9)]

Whenever the Permittee submits information under a claim of confidentiality pursuant to 15A NCAC 2Q .0107, the Permittee may also submit a copy of all such information and claim directly to the EPA upon request. All requests for confidentiality must be in accordance with 15A NCAC 2Q .0107.

Z. **Construction and Operation Permits** [15A NCAC 2Q .0100 and .0300]

A construction and operating permit shall be obtained by the Permittee for any proposed new or modified facility or emission source which is not exempted from having a permit prior to the beginning of construction or modification, in accordance with all applicable provisions of 15A NCAC 2Q .0100 and .0300.

AA. **Standard Application Form and Required Information** [15A NCAC 2Q .0505 and .0507]

The Permittee shall submit applications and required information in accordance with the provisions of 15A NCAC 2Q .0505 and .0507.

BB. **Financial Responsibility and Compliance History** [15A NCAC 2Q .0507(d)(3)]

The DAQ may require an applicant to submit a statement of financial qualifications and/or a statement of substantial compliance history.

CC. **Refrigerant Requirements (Stratospheric Ozone and Climate Protection)** [15A NCAC 2Q .0501(e)]

1. If the Permittee has appliances or refrigeration equipment, including air conditioning equipment, which use Class I or II ozone-depleting substances such as chlorofluorocarbons and hydrochlorofluorocarbons listed as refrigerants in 40 CFR Part 82 Subpart A Appendices A and B, the Permittee shall service, repair, and maintain such equipment according to the work practices, personnel certification requirements, and certified recycling and recovery equipment specified in 40 CFR Part 82 Subpart F.
2. The Permittee shall not knowingly vent or otherwise release any Class I or II substance into the environment during the repair, servicing, maintenance, or disposal of any such device except as provided in 40 CFR Part 82 Subpart F.
3. The Permittee shall comply with all reporting and recordkeeping requirements of 40 CFR 82.166. Reports shall be submitted to the EPA or its designee as required.

DD. **Prevention of Accidental Releases - Section 112(r)** [15A NCAC 2Q .0508(h)]

If the Permittee is required to develop and register a Risk Management Plan with EPA pursuant to Section 112(r) of the Clean Air Act, then the Permittee is required to register this plan in accordance with 40 CFR Part 68.

EE. **Prevention of Accidental Releases General Duty Clause - Section 112(r)(1) - FEDERALLY-ENFORCEABLE ONLY**

Although a risk management plan may not be required, if the Permittee produces, processes, handles, or stores any amount of a listed hazardous substance, the Permittee has a general duty to take such steps as are necessary to prevent the accidental release of such substance and to minimize the consequences of any release.

FF. **Title IV Allowances** [15A NCAC 2Q .0508(i)(1)]

This permit does not limit the number of Title IV allowances held by the Permittee, but the Permittee may not use allowances as a defense to noncompliance with any other applicable requirement. The Permittee's emissions may not exceed any allowances that the facility lawfully holds under Title IV of the Federal Clean Air Act.

GG. **Air Pollution Emergency Episode** [15A NCAC 2D .0300]

Should the Director of the DAQ declare an Air Pollution Emergency Episode, the Permittee will be required to operate in accordance with the Permittee's previously approved Emission Reduction Plan or, in the absence of an approved plan, with the appropriate requirements specified in 15A NCAC 2D .0300.

HH. **Registration of Air Pollution Sources** [15A NCAC 2D .0200]

The Director of the DAQ may require the Permittee to register a source of air pollution. If the Permittee is required to register a source of air pollution, this registration and required information will be in accordance with 15A NCAC 2D .0202(b).

II. **Ambient Air Quality Standards** [15A NCAC 2D .0501(e)]

In addition to any control or manner of operation necessary to meet emission standards specified in this permit, any source of air pollution shall be operated with such control or in such manner that the source shall not cause the ambient air quality standards in 15A NCAC 2D .0400 to be exceeded at any point beyond the premises on which the source is located. When controls more stringent than named in the applicable emission standards in this permit are required to prevent violation of the ambient air quality standards or are required to create an offset, the permit shall contain a condition requiring these controls.

JJ. **General Emissions Testing and Reporting Requirements** [15A NCAC 2Q .0508(i)(16)]

If emissions testing is required by this permit or the DAQ or if the Permittee submits emissions testing to the DAQ in support of a permit application, the Permittee shall perform such testing in accordance with the appropriate EPA reference method(s) as approved by the DAQ and follow the procedures outlined below. The Permittee must request **in writing** and receive approval from the DAQ for an alternate test method or procedure.

1. The Permittee shall submit a completed Protocol Submittal Form to the DAQ Regional Supervisor at least 45 days prior to the scheduled test date. A copy of the Protocol Submittal Form may be obtained from the Regional Supervisor.
2. The Permittee shall notify the Regional Supervisor of the specific test dates at least 15 days prior to testing in order to afford the DAQ the opportunity to have an observer on-site during the sampling program.
3. During all sampling periods, the Permittee shall operate the emission source(s) under maximum normal operating conditions or alternative operating conditions as deemed appropriate by the Regional Supervisor or his delegate.
4. The Permittee shall submit **two** copies of the test report to the DAQ. The test report shall contain at a minimum the following information:
 - a. a certification of the test results by sampling team leader and facility representative;
 - b. a summary of emissions results and text detailing the objectives of the testing program, the applicable state and federal regulations, and conclusions about the testing and compliance status of the emission source(s);
 - c. a detailed description of the tested emission source(s) and sampling location(s) process flow diagrams, engineering drawings, and sampling location schematics should be included as necessary;
 - d. all field, analytical, and calibration data necessary to verify that the testing was performed as specified in the applicable test methods;
 - e. example calculations for at least one test run using equations in the applicable test methods and all test results including intermediate parameter calculations; and
 - f. documentation of facility operating conditions during all testing periods and an explanation relating these operating conditions to maximum normal operation. If necessary, provide historical process data to verify maximum normal operation.
5. The testing requirement(s) shall be considered satisfied only upon written approval of the test results by the DAQ.
6. The DAQ will review emission test results with respect exclusively to the specified testing objectives as proposed by the Permittee and approved by the DAQ. The use of the test results beyond the stated objectives remains subject to the approval of the DAQ.

KK. **Reopening for Cause** [15A NCAC 2Q .0517]

1. A permit shall be reopened and revised under the following circumstances:
 - a. additional applicable requirements become applicable to a facility with remaining permit term of three or more years;
 - b. additional requirements (including excess emission requirements) become applicable to a source covered by Title IV;
 - c. the Director or EPA finds that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit; or
 - d. the Director or EPA determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
2. Any permit reopening shall be completed or a revised permit issued within 18 months after the applicable requirement is promulgated. No reopening is required if the effective date of the requirement is after the expiration of the permit term unless the term of the permit was extended pursuant to 15A NCAC 2Q .0513(c).
3. Except for the state-enforceable only portion of the permit, the procedures set out in 15A NCAC 2Q .0507, .0521, or .0522 shall be followed to reissue the permit. If the State-enforceable only portion of the permit is reopened, the procedures in 15A NCAC 2Q .0300 shall be followed. The proceedings shall affect only those parts of the permit for which cause to reopen exists.
4. The Director shall notify the Permittee at least 60 days in advance of the date that the permit is to be reopened, except in cases of imminent threat to public health or safety the notification period may be less than 60 days.
5. Within 90 days, or 180 days if the EPA extends the response period, after receiving notification from the EPA that a permit needs to be terminated, modified, or revoked and reissued, the Director shall send to the EPA a proposed determination of termination, modification, or revocation and reissuance, as appropriate.

LL. **Reporting Requirements for Non-Operating Equipment** [15A NCAC 2Q .0508(i)(16)]

The Permittee shall maintain a record of operation for permitted equipment noting whenever the equipment is taken from and placed into operation. During operation the monitoring recordkeeping and reporting requirements as prescribed by the permit shall be implemented within the monitoring period.

ATTACHMENT

List of Acronyms

AOS	Alternate Operating Scenario
BACT	Best Available Control Technology
Btu	British thermal unit
CEM	Continuous Emission Monitor
CFR	Code of Federal Regulations
CAA	Clean Air Act
DAQ	Division of Air Quality
DENR	Department of Environment and Natural Resources
EMC	Environmental Management Commission
EPA	Environmental Protection Agency
FR	Federal Register
GACT	Generally Available Control Technology
HAP	Hazardous Air Pollutant
MACT	Maximum Achievable Control Technology
NCAC	North Carolina Administrative Code
NCGS	North Carolina General Statutes
NESHAPS	National Emission Standards for Hazardous Air Pollutants
NO_x	Nitrogen Oxides
NSPS	New Source Performance Standard
OAH	Office of Administrative Hearings
PM	Particulate Matter
PM₁₀	Particulate Matter with Nominal Aerodynamic Diameter of 10 Micrometers or Less
POS	Primary Operating Scenario
PSD	Prevention of Significant Deterioration
SIC	Standard Industrial Classification
SIP	State Implementation Plan
SO₂	Sulfur Dioxide
tpy	Tons Per Year
VOC	Volatile Organic Compound